

# **PRODUCT DATASHEET** ST CLAS A 40 5.5 W/6500K E27

# LED STAR CLASSIC A | LED lamps, classic bulb shape



## AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### **PRODUCT FEATURES**

- LED alternative to conventional lamps
- Mercury-free lamps



## **TECHNICAL DATA**

#### Electrical data


Rated wattage	5.50 W
Nominal wattage	5.50 W
Nominal voltage	220240 V
Max. lamp no. on circuit break. 10 A (B)	170
Max. lamp no. on circuit break. 16 A (B)	272
Operating frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	40 W

#### Photometrical data

Rated luminous flux	470 lm
	470 011
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Luminous flux	470 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm
Rated color temperature	6500 K
Color rendering index Ra	≥80

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

## Dimensions & weight



Overall length

95.0 mm

## PRODUCT DATASHEET

Diameter	55.0 mm
Outer bulb	A55
Length	95.0 mm

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	92 °C

## Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

## Additional product data

Base (standard designation)	E27	
Mercury-free	Yes	
Design / version	Frosted	
Show WEEE picto Product remark	Show WEEE picto Yes	Yes
	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Mercury content	0.0 mg	
Capabilities Dimmable	Νο	

## Certificates & standards

Energy efficiency class	A+
Energy consumption	6 kWh/1000h

## Country-specific categorizations

der reference	LEDSCLA40 5,5W/
---------------	-----------------

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075304192	Folding carton box 1	55 mm x 55 mm x 94 mm	30.00 g	0.28 dm³

4058075304208	Shipping carton box	287 mm x 122 mm x 103 mm	381.00 g	3.61 dm³
	10			

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **REFERENCES / LINKS**

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.