

# PRODUCT DATASHEET

## SUN@Home Downlight Slim 225mm

Sun@Home Downlights | Downlight with Human Centric Lighting Technology

---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



---

### Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and –intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

---

### Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

---

## TECHNICAL DATA

### Electrical data

Nominal wattage	22.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	150.000 mA
Inrush current	30 A
Max. number of luminaires per miniature circuit breaker B16	5
Max. number of luminaires per miniature circuit breaker C10	5
Max. number of luminaires per miniature circuit breaker C16	8
Power factor $\lambda$	> 0.70
Protection class	II
Operating mode	Mains voltage

### Photometrical data

Luminous flux	1500 lm
Total luminous flux of contained light sources	1950 lm
Luminous efficacy	75 lm/W
Color temperature	2200...5000 K
Reference control setting of contained light source (Kelvin)	2700 K
Light color (designation)	Tunable White
Color rendering index Ra	> 95
Standard deviation of color matching	≤6 sdcn
Flickering metric (Pst LM)	≤ 1 %
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110 °

### Dimensions & Weight

Diameter	225.00 mm
Height	33.50 mm
Product weight	273.00 g

HCL SMART Downlight 225 TW

## Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Cover material	Polystyrene (PS)
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+60 °C
Type of connection	Terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	200 mm
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

## Emergency lighting

Luminous flux in maintained operation mode	-
--	---

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable






## EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SUN@HOME DOWNLIGHT SLIM
	Legal information	SUN@HOME
	Declarations of conformity	SUN@HOME Downlight Slim
	Declarations of conformity UKCA	SMART WIFI AND SUNATHOME DOWNLIGHT SLIM
CAD/BIM files		Document name
	BIM Step 3D	Sun@Home DL Slim 225

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075575851	Folding box 1	42 mm x 234 mm x 238 mm	358.00 g	2.34 dm <sup>3</sup>
4058075575868	Shipping box 6	262 mm x 240 mm x 247 mm	2330.00 g	15.53 dm <sup>3</sup>
4058075657106	Shipping box 24	544 mm x 500 mm x 272 mm	10626.00 g	73.98 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.