

# PRODUCT DATASHEET

## LB FLEX 1200 P 73W 840 VW

LOW BAY FLEX 1200 | Low-bay luminaires with attractive linear design, up to 155 lm/W



### Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Warehouses
- Logistics halls
- Industrial and storage facilities
- Discounters, supermarkets
- Sports halls
- Indoor sports facilities

### Product benefits

- Economical thanks to high luminous efficacy up to 155 lm/W
- Easy and quick installation thanks to toolless connector box with 5- and 7-pole terminals
- Modern and robust design
- 5 years guarantee

### Product features

- Different luminous flux and beam angle for mounting heights of ~ 4 m to ~10 m in 4000 K
- Through-wiring cable already installed
- Long Lifetime (L80/B10): up to 100,000 h
- High color consistency:  $\leq 3$  SDCM




---

**TECHNICAL DATA****Electrical data**

|                                                             |                               |
|-------------------------------------------------------------|-------------------------------|
| Nominal wattage                                             | 73 W                          |
| Nominal voltage                                             | 220...240 V                   |
| Mains frequency                                             | 50...60 Hz                    |
| Nominal current                                             | 320 mA                        |
| Inrush current                                              | 25.24 A                       |
| Inrush current time $T_{h50}$                               | 436 $\mu$ s                   |
| Max. number of luminaires per miniature circuit breaker B16 | 13                            |
| Max. number of luminaires per miniature circuit breaker C10 | 13                            |
| Max. number of luminaires per miniature circuit breaker C16 | 22                            |
| Power factor $\lambda$                                      | $\geq 0.90$                   |
| Total harmonic distortion                                   | $\leq 20$ %                   |
| Protection class                                            | I                             |
| Operating mode                                              | ELECTRONIC CONTROL GEAR (ECG) |

**Photometrical data**


|                                              |                      |
|----------------------------------------------|----------------------|
| Luminous flux                                | 11315 lm             |
| Luminous efficacy                            | 155 lm/W             |
| Color temperature                            | 4000 K               |
| Light color (designation)                    | Cool White           |
| Color rendering index Ra                     | $\geq 80$            |
| Standard deviation of color matching         | < 3 sdc <sub>m</sub> |
| Low flicker                                  | Yes                  |
| Photobiological safety group acc. to EN62778 | RG1                  |
| Photobiological safety group acc. to EN62471 | RG1                  |
| Beam angle                                   | 120 °                |




LB FLEX 1200 P 73W 840 VW



LB FLEX 200 P 73W 840 VW WITH  
BP COVER



LB FLEX 200 P 73W 840 VW WITH  
BP COVER



LB FLEX 1200 P 73W 840 VW

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 1236 mm   |
| Width          | 115.00 mm |
| Height         | 65.00 mm  |
| Product weight | 3400.00 g |



LOW BAY FLEX 1200

## Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | White              |
| Housing color                              | White              |
| Body material                              | Steel              |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

## Application & Mounting

|                                        |                    |
|----------------------------------------|--------------------|
| Ambient temperature range              | -25...+50 °C       |
| Temperature range at storage           | -20...+80 °C       |
| Type of connection                     | Screwless terminal |
| Type of protection                     | IP23               |
| Protection class IK (shock resistance) | IK08               |
| Dimmable                               | No                 |
| Mounting type                          | Surface/Suspended  |
| Mounting location                      | Ceiling            |
| Application environment                | Indoor             |
| Adjustable                             | No                 |
| With light source                      | Yes                |

## Lifespan

|                            |                        |
|----------------------------|------------------------|
| Lifespan L70/B50 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C  | 100000 h               |
| Lifespan L90/B10 at 25 °C  | 83000 h                |
| Number of switching cycles | 50000                  |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Control gear

|                             |        |
|-----------------------------|--------|
| Output current              | 310 mA |
| ECG - Output ripple current | < 10 % |

## Certificates & Standards

|                                                      |                                             |
|------------------------------------------------------|---------------------------------------------|
| Standards                                            | CE / CB / ENEC / TÜV SÜD / EAC / UKCA / EPD |
| Luminaire with limited surface temperature, "D sign" | No                                          |
| Ball shot safe                                       | No                                          |
| EPD                                                  | LEDV-00020-V01.01-EN                        |
| Replaceable light source (EPREL)                     | Not replaceable                             |

### Accessories Optional

| Product image                                                                     | Product name           | EAN           |
|-----------------------------------------------------------------------------------|------------------------|---------------|
|  | LB FLEX SUSPENSION KIT | 4058075693722 |

### EQUIPMENT / ACCESSORIES

– Suspension kit, ball-proof cover and angulation mounting kit available as separate accessory

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                          |
|------------------------------------------------------------------------------------|----------------------------------------|----------------------------------------|
|  | User instruction / safety instructions | UI Lowbay Flex                         |
|  | Legal information                      | Legal Insert LB FLEX                   |
|  | Legal information                      | LS Insert LB FLEX DALI                 |
|  | Legal information                      | Informationstext 18 Abs 4 ElektroG     |
|  | Declarations of conformity             | EU Declaration of conformity LB FLEX   |
|  | Declarations of conformity UKCA        | LB FLEX 840                            |
| Photometric and lighting design files                                              |                                        | Document name                          |
|  | IES file (IES)                         | LB FLEX 1200 P 73W 840 VW              |
|  | IES file (IES)                         | LB FLEX 200 P 73W 840 VW WITH BP COVER |

| Photometric and lighting design files                                               |                                     | Document name                           |
|-------------------------------------------------------------------------------------|-------------------------------------|-----------------------------------------|
|    | LDT file (Eulumdat)                 | LB FLEX 1200 P 73W 840 VW               |
|    | LDT file (Eulumdat)                 | LB FLEX 1200 P 73W 840 VW WITH BP COVER |
|    | ULD file (DIALux)                   | LB FLEX 1200 P 73W                      |
|    | ROLF file (RELUX)                   | LB FLEX 1200 P                          |
|    | UGR file (UGR table)                | LB FLEX 1200 P 73W 840 VW               |
|    | UGR file (UGR table)                | LB FLEX 200 P 73W 840 VW WITH BP COVER  |
|    | Light distribution curve type cone  | LB FLEX 1200 P 73W 840 VW               |
|    | Light distribution curve type cone  | LB FLEX 200 P 73W 840 VW WITH BP COVER  |
|    | Light distribution curve type polar | LB FLEX 1200 P 73W 840 VW               |
|    | Light distribution curve type polar | LB FLEX 200 P 73W 840 VW WITH BP COVER  |
| CAD/BIM files                                                                       |                                     | Document name                           |
|  | BIM Revit 3D                        | LOW BAY FLEX                            |
|  | CAD STEP 3D                         | LB FLEX 1200                            |
| Tender texts                                                                        |                                     | Document name                           |
|  | Tender documents                    | LOW BAY FLEX 1200 P 73W 840 VW-EN       |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075676121 | Folding box<br>1             | 106 mm x 1,282 mm x 154 mm           | 4255.00 g    | 20.93 dm³ |
| 4058075676138 | Shipping box<br>3            | 1,312 mm x 488 mm x 143 mm           | 13901.00 g   | 91.56 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.