



PRODUCT DATASHEET

SMART+ Wifi Planon 1200x100mm RGB + TW

SMART+ Planon Frameless TW and Multicolor | Frameless panel luminaires with WiFi technology

Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

| | |
|---|---------------|
| Nominal wattage | 35.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 176.000 mA |
| Max. number of luminaires per miniature circuit breaker B16 | 16 |
| Max. number of luminaires per miniature circuit breaker C16 | 24 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | II |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|---------------------|
| Luminous flux | 2500 lm |
| Total luminous flux of contained light sources | 4100 lm |
| Luminous efficacy | 71 lm/W |
| Color temperature | 3000...6500 K |
| Light color (designation) | Tunable White / RGB |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 6 sdcm |
| Flickering metric (Pst LM) | ≤ 1 |
| Stroboscope effect metric (SVM) | ≤ 0.4 |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1200.00 mm |
| Width | 100.00 mm |
| Height | 64.00 mm |
| Product weight | 2630.00 g |

SMART WIFI PLANON
FRAMELESS120X10

Materials & Colors

| | |
|--|-------------------------------|
| Product color | White |
| Housing color | White |
| Body material | Aluminum |
| Cover material | Polymethylmethacrylate (PMMA) |
| Light emitting surface material | PMMA |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|-------------------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP20 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Mounting location | Ceiling |
| Application environment | Indoor |
| With light source | No |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 25000 h |
| Number of switching cycles | 15000 |

Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| | |
|----------------|--|
| Product remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|----------------|--|

EQUIPMENT / ACCESSORIES





– Mounting bracket included

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|---|--|-------------------------------------|
|  | User instruction / safety instructions | SMART+ PLANON FRAMELESS |
|  | User instruction / safety instructions | SMART+ PLANON FRAMELESS |
|  | Declarations of conformity | SMART WIFIPLANONFRAMELESS120X10RGBW |
|  | Declarations of conformity UKCA | SMART WIFI AND SUNATHOME |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075484573 | Folding box 1 | 95 mm x 1,237 mm x 135 mm | 2928.00 g | 15.86 dm ³ |
| 4058075484580 | Shipping box 6 | 1,254 mm x 304 mm x 305 mm | 19064.00 g | 116.27 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.