

# PRODUCT DATASHEET SMART+ Wifi Planon Plus Frame 450x450mm RGB + TW

SMART+ Planon Plus RGBW | Panel luminaires with WiFi technology



## Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

## **Product benefits**

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi



# TECHNICAL DATA

## Electrical data


Nominal wattage	24.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	100.000 mA	
Inrush current	16.1 A	
Inrush current time T <sub>h50</sub>	125 μs	
Max. number of luminaires per miniature circuit breaker B16	37	
Max. number of luminaires per miniature circuit breaker C16	47	
Power factor $\lambda$	> 0.70	
Total harmonic distortion	< 30 %	
Protection class	П	
Operating mode	Mains voltage	

# Photometrical data

Luminous flux	1750 lm
Total luminous flux of contained light sources	2500 lm
Luminous efficacy	72 lm/W
Color temperature	27006500 K
Light color (designation)	Tunable White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °
UGR	< 25

# Dimensions & Weight

Length	450.00 mm
Width	450.00 mm
Height	51.00 mm
Product weight	2140.00 g



## Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	25000

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Replaceable light source (EPREL)	Not replaceable
Additional product data	
Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.

## **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SMART+ PLANON PLUS	
PDF	Extended installation guide	SMART+ WIFI INSTALLATION GUIDE	
PDF	Declarations of conformity	SMART WIFIPLANPLUS	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075752627	Folding box 1	72 mm x 497 mm x 487 mm	2401.00 g	17.43 dm <sup>3</sup>
4058075752634	Shipping box 2	522 mm x 162 mm x 517 mm	5428.00 g	43.72 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.