

PRODUCT DATASHEET

TRUSYS FLEX P RAIL 600 8P WT

TruSys® FLEX ENERGY RAIL 8-POLE | 8-pole mounting rail

Areas of application

- Industry halls, high rack warehouse, hardware stores



Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)
- Version of 600 mm rail to be used with TRUSYS FLEX SENSOR TRACK

Product features

- Through wired with 8 core cable
- Different lengths available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors




TECHNICAL DATA

Electrical data

Protection class	I
------------------	---

Dimensions & Weight

Length	750 mm
Width	70.2 mm
Height	38.8 mm
Product weight	890.00 g



TRUSYS FLEX P RAIL 600 8P WT

Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

Mounting location	Ceiling
With light source	No





Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
-----------	-----------------------------

EQUIPMENT / ACCESSORIES

– Various accessories available

DOWNLOAD DATA

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	TRUSYS FLEX RAIL ST COVER
	Declarations of conformity UKCA	TRUSYS FLEX RAIL ST COVER
Tender texts		Document name
	Tender documents	TruSys FLEX ENERGY RAIL 8 POLE 600 8P WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854193521	Sleeve 1	150 mm x 233 mm	907.00 g	
4099854193538	Shipping box 4	822 mm x 193 mm x 145 mm	4247.00 g	23.00 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.