

## PRODUCT DATASHEET

### DULUX LED D18 VT EM & AC MAINS 7.5W 830 G24D

OSRAM DULUX LED D VT EM & AC MAINS | LED replacement for CFLni with 2-pin G24d base for CCG



#### Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

#### Product benefits

- Easy installation
- Low energy consumption
- Easy relamping thanks to compact design
- Operation directly on 230 V AC mains possible

#### Product features

- LED replacement for conventional compact fluorescent lamps for use in CCG luminaires or on AC mains
- Only suitable for vertical application
- Lifetime up to 30,000 h
- Single-ended two-pin plug-in G24d base
- Type of protection: IP20
- Mercury-free lamps



---


**TECHNICAL DATA****Electrical data**

|  |                                     |
|--|-------------------------------------|
| Nominal wattage  | 7.5 W                               |
| Construction wattage                                     | 7.50 W                              |
| Nominal voltage  | 220...240 V                         |
| Operating mode   | Conventional control gear (CCG), AC |
| Nominal current  | 34 mA                               |
| Type of current  | AC                                  |
| Inrush current   | 15.6 A                              |
| Suitable for DC input                                    | Yes                                 |
| Input voltage DC   | 186...260 V <sup>1)</sup>           |
| Operating frequency                                      | 50/60 Hz                            |
| Mains frequency  | 50/60 Hz                            |
| Max. lamp number on MCB B10 A                            | 38                                  |
| Max. lamp number on MCB B10 A - CCG without compensation | 118                                 |
| Max. lamp number on MCB B10 A - CCG with compensation    | 8                                   |
| Max. lamp number on MCB B16 A                            | 48                                  |
| Max. lamp number on MCB B16 A - CCG without compensation | 188                                 |
| Max. lamp number on MCB B16 A - CCG with compensation    | 11                                  |
| Total harmonic distortion                                | ≤ 30 %                              |

<sup>1)</sup> Permitted voltage range

**Photometrical data**

|                                 |            |
|---------------------------------|------------|
| Luminous flux                   | 870 lm     |
| Luminous efficacy               | 116 lm/W   |
| Light color (designation)       | Warm White |
| Color temperature               | 3000 K     |
| Color rendering index Ra        | 80         |
| Light color                     | 830        |
| Flickering metric (Pst LM)      | 1.0        |
| Stroboscope effect metric (SVM) | 0.4        |



EPREL data spectral diagram PROF  
LEDr 3000K

Dimensions & Weight



|                |           |
|----------------|-----------|
| Overall length | 124.00 mm |
| Diameter       | 37.70 mm  |
| Tube diameter  | 35 mm     |
| Product weight | 85.00 g   |

Temperatures & operating conditions

|                                      |                            |
|--------------------------------------|----------------------------|
| Ambient temperature range            | -20...+45 °C <sup>1)</sup> |
| Maximum temperature at tc test point | 70 °C                      |

1) Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

|                           |         |
|---------------------------|---------|
| Lifespan L70/B50 at 25 °C | 30000 h |
|---------------------------|---------|

Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | G24d    |
| Mercury-free                | Yes     |
| Design / version            | Frosted |

Certificates & Standards

|                    |                 |
|--------------------|-----------------|
| Type of protection | IP20            |
| Standards          | CE / EAC / UKCA |

|  |     |
|--|-----|
| Photobiological safety group acc. to EN62778 | RG0 |
|--|-----|

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | DULUX LED D18 V |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015















|  |   |
|--|---|
| Lighting technology used                             | LED                                     |
| Non-directional or directional                       | NDLS                                    |
| Mains or non-mains                                   | MLS                                     |
| Light source cap-type (or other electric interface)  | G24d                                    |
| Connected light source (CLS)                         | No                                      |
| Color-tuneable light source                          | No                                      |
| Envelope   | No                                      |
| High luminance light source                          | No                                      |
| Anti-glare shield                                    | No                                      |
| Claim of equivalent power                            | No                                      |
| Length   | 124.00 mm                               |
| Height   | 37.70 mm                                |
| Width  | 37.70 mm                                |
| Chromaticity coordinate x                            | 0.440                                   |
| Chromaticity coordinate y                            | 0.403                                   |
| R9 Colour rendering index                            | 0.00                                    |
| Beam angle correspondence                            | SPHERE_360                              |
| Survival factor                                      | 0,90                                    |
| Displacement factor                                  | 0,90                                    |
| LED light source replaces a fluorescent light source | No                                      |
| EPREL ID   | 1404740,1412873,2206844,2324434         |
| Model number   | AC46428,AC47824,AC47824,AC71121,AC81514 |

### Safety advice

- Not suitable for tandem operation.
- The operating temperature range of DULUX LED is restricted. In case of doubt regarding suitability of the application please measure T<sub>c</sub> temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

| Documents and certificates   |  | Document name                               |
|--|--|---|
|    | User instruction / safety instructions | OSRAM DULUX LED D VERTICAL                  |
|    | Legal information                      | Informationstext 18 Abs 4 ElektroG          |
|    | Declarations of conformity             | DULUXLED                                    |
|    | Declarations of conformity             | LEDTUBE                                     |
|    | Declarations of conformity UKCA        | DULUX LED                                   |
|    | Declarations of conformity UKCA        | LEDTUBE                                     |
| Photometric and lighting design files  |  | Document name                               |
|  | IES file (IES)                         | DULUX LED D18 VT EM 7.5W 830 G24D           |
|  | IES file (IES)                         | DULUX LED D18 VT EM 7.5W 830 G24D OSRAM     |
|  | LDT file (Eulumdat)                    | DULUX LED D18 VT EM 7.5W 830 G24D           |
|  | LDT file (Eulumdat)                    | DULUX LED D18 VT EM 7.5W 830 G24D OSRAM     |
|  | UGR file (UGR table)                   | DULUX LED D18 VT EM 7.5W 830 G24D OSRAM     |
|  | Light distribution curve type polar    | DULUX LED D18 VT EM 7.5W 830 G24D           |
|  | Light distribution curve type polar    | DULUX LED D18 VT EM 7.5W 830 G24D OSRAM     |
|  | Spectral power distribution            | EPREL data spectral diagram PROF LEDr 3000K |

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|--------------|------------------------------|--------------------------------------|--------------|--------|
|--------------|------------------------------|--------------------------------------|--------------|--------|

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075824539 | Folding box<br>1             | 41 mm x 49 mm x 128 mm               | 98.00 g      | 0.26 dm <sup>3</sup> |
| 4099854109812 | Shipping box<br>10           | 222 mm x 111 mm x 140 mm             | 1089.00 g    | 3.45 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.