

# PRODUCT DATASHEET

## SMART+ MATTER Classic A75 9.5W

### 827...865 Multicolor E27

SMART+ MATTER CLASSIC A MULTICOLOR | Classic A bulb shape with Matter technology



#### Areas of application

- General illumination through smart home technology
- Professional applications (hotels, bars, boutiques etc.) utilizing dynamic and robust ambient lighting effects
- When users want to mix and match smart home products from different manufacturers
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Wireless control via app or voice control
- Seamless integration with Matter-compatible systems
- Simplified set up process due to the standard user-friendly installation steps
- Enhanced security by implementing strong encryption and authentication protocols
- Lower energy consumption than incandescent or halogen lamps

#### Product features

- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0) or any other Matter-compatible platforms
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: Matter over WiFi
- Lifetime: up to 20,000 h



- Compatible with Alexa, Google Home, Apple Home and other Matter-compatible platforms


TECHNICAL DATA

Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 9.5 W       |
| Construction wattage                   | 9.50 W      |
| Nominal voltage                        | 220...240 V |
| Nominal current                        | 75 mA       |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Power factor $\lambda$                 | 0.50        |
| Claimed equiv. conventional lamp power | 75 W        |
| Operating mode                         | AC Mains    |

Photometrical data

|                                         |                           |
|-----------------------------------------|---------------------------|
| Light color (designation)               | RGBW                      |
| Lumen main.fact.at end of nom.life time | 0.95                      |
| Standard deviation of color matching    | $\leq 6$ sdc <sub>m</sub> |
| Nominal luminous flux                   | 1055 lm                   |
| Luminous flux                           | 1055 lm                   |
| Luminous efficacy                       | 111 lm/W                  |
| Adjustable color temperature            | 2700...6500 K             |
| Color temperature                       | 2700...6500 K             |
| Color rendering index Ra                | $\geq 80$                 |
| Flickering metric (Pst LM)              | $\leq 1$                  |
| Stroboscope effect metric (SVM)         | $\leq 0.4$                |



SMART MATTER CLA75 RGBW

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 200 °    |
| Starting time       | < 0.5 s  |
| Warm-up time (60 %) | < 0.50 s |

Dimensions & Weight



|                    |           |
|--------------------|-----------|
| Product weight     | 43.00 g   |
| Diameter           | 60.00 mm  |
| Maximum diameter   | 60 mm     |
| Length             | 112.00 mm |
| Width              | 60.00 mm  |
| Height             | 60.00 mm  |
| Outer bulb [PICOS] | A60       |

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Number of switching cycles                   | 100000  |
| Lifespan                                     | 20000 h |
| Lumen maintenance at end of service lifetime | 0.95    |

Colors & materials

|               |         |
|---------------|---------|
| Product color | White   |
| Housing color | White   |
| Body material | Plastic |

Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Additional product data

|              |     |
|--------------|-----|
| Mercury-free | Yes |
|--------------|-----|

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
| Base (standard designation) | E27                                                                                                                                                                                                                                                                                                                                          |

### Capabilities

|          |                   |
|----------|-------------------|
| Dimmable | Yes <sup>1)</sup> |
|----------|-------------------|

<sup>1)</sup> Via App

### Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | E <sup>1)</sup> |
| Energy consumption      | 10.00 kWh/1000h |
| Standards               | CE / UKCA       |
| Type of protection      | IP20            |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Energy labelling regulation data acc EU 2019/2015

|                                                     |             |
|-----------------------------------------------------|-------------|
| Lighting technology used                            | LED         |
| Non-directional or directional                      | NDLS        |
| Mains or non-mains                                  | MLS         |
| Light source cap-type (or other electric interface) | E27         |
| Connected light source (CLS)                        | Yes         |
| Color-tuneable light source                         | Yes         |
| Envelope                                            | No          |
| High luminance light source                         | No          |
| Anti-glare shield                                   | No          |
| Correlated colour temperature type                  | RANGE       |
| Networked standby power for CLS                     | <0.5 W      |
| Claim of equivalent power                           | Yes         |
| Chromaticity coordinate x                           | 0.457-0.313 |
| Chromaticity coordinate y                           | 0.410-0.328 |
| R9 Colour rendering index                           | >0          |
| Beam angle correspondence                           | SPHERE_360  |
| Survival factor                                     | 0.9         |
| Displacement factor                                 | >0.7        |

|                                                      |                 |
|------------------------------------------------------|-----------------|
| LED light source replaces a fluorescent light source | No              |
| EPREL ID                                             | 1694299         |
| Model number                                         | AC52855,AC52855 |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

| Documents and certificates                                                          |                                 | Document name                         |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------------|
|     | Extended installation guide     | Insert WIFI MATTER StartUpG Lamps LDV |
|     | Declarations of conformity      | CE Declaration Smart Matter Classic   |
|     | Declarations of conformity UKCA | UKCA Declaration Smart Matter Classic |
| Photometric and lighting design files                                               |                                 | Document name                         |
|  | Spectral power distribution     | SMART MATTER CLA75 RGBW               |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854194849 | Folding box<br>1             | 61 mm x 96 mm x 154 mm               | 117.00 g     | 0.90 dm <sup>3</sup> |
| 4099854194856 | Shipping box<br>4            | 210 mm x 165 mm x 135 mm             | 601.00 g     | 4.68 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.