

## PRODUCT DATASHEET

### QT-ECO 1X4...16 S

QUICKTRONIC® ECONOMIC | ECG for FL 7 mm and CFL



#### Areas of application

- Public buildings

#### Product benefits

- Compact housing
- Automatic restart after lamp replacement
- Large input voltage range

#### Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz
- Energy Efficiency Index EEI: A2 / A3 (depending on lamp)
- Automatic shutdown of defective lamps and at end of life (EoL)

## TECHNICAL DATA

### Electrical data

Nominal wattage	13.00 W
Nominal voltage	220...240 V
Input voltage DC	176...254 V
U-OUT (working voltage)	250 V
Inrush current	10 A
Mains frequency	50 Hz <sup>1)</sup>
Max. ECG no. on circuit breaker 10 A (B)	68
Max. ECG no. on circuit breaker 16 A (B)	112
Operating frequency	35...45 kHz

<sup>1)</sup> Approximately

### Light technical data

Starting time	1 s
---------------	-----

### Dimensions & Weight

Length	80.00 mm
Mounting hole spacing, length	72,0...75,0 mm
Width	40.00 mm
Height	22.00 mm
Product weight	50.00 g

### Colors & materials

Casing material	Plastic
Body material	Plastic

### Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Maximum temperature at tc test point	70 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

### Lifespan

ECG lifetime	30000 h <sup>1)</sup>
--------------	-----------------------

<sup>1)</sup> T<sub>c</sub> = 70°C, with max. 10% failure rate

### Capabilities

Dimmable	No
Max. cable length to lamp/LED module	1.0 m / 0.5 m
Suitable for fixtures with prot. class	I / II
End of lamp life safety shutdown	EOL T.2







### Certificates & Standards


Approval marks – approval	VDE
Standards	Acc. to EN 61347-2-3 / Acc. to EN 55015:2006 + A1:2007 / Acc. to EN 61000-3-2 / Acc. to EN 61547
Protection class	I
Type of protection	IP20
Energy efficiency class	A3
EEL – Energy Label	A3

### LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

### DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	592501_EAC QT-ECO
	Declarations of conformity	339525_Declaration of Conformity (GB)
	Certificates	683440_VDE-Marks approvals
	Certificates	334983_VDE-Marks approval
	Certificates	335154_Manufacturer's declaration – EN 55015:2006+A1:2007 (300 MHz)
	Certificates	334955_VDE-Marks approval

CAD/BIM files		Document name
	CAD data 3D PDF	313386_80x40x22 9900019

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300638584	Unpacked 1		51.00 g	
4050300655260	Shipping box 50	212 mm x 142 mm x 170 mm	2791.00 g	5.12 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.