

# PRODUCT DATASHEET

## Submarine Integrated Slim Value 1.2M 18W 4000K

SUBMARINE® Integrated Slim Value | Flat and slim dampproof luminaires with integrated LED module

---

### Areas of application

- Basements, garages, warehouses



---

### Product benefits

- Easy installation, no tools required for connection
- Impressive for its low-profile design

---

### Product features

- Damp-proof luminaires
- Dust-protected and jet-proof (IP65)
- Extremely low profile
- Not dimmable



TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	170.000 mA
Max. number of luminaires per miniature circuit breaker B16	46
Max. number of luminaires per miniature circuit breaker C16	59
Power factor $\lambda$	> 0.5
Total harmonic distortion	< 20 %
Protection class	II

Photometrical data

Luminous flux	1600 lm
Total luminous flux of contained light sources	1900 lm
Luminous efficacy	89 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	< 5 sdcm
Flickering metric (Pst LM)	<10
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

Dimensions & Weight

Length	1245.00 mm
Width	53.00 mm
Height	35.00 mm
Product weight	299.00 g



SUBMARINE I SLIM VALUE 1.2M  
840

## Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-20...+35 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

## Additional product data

Number of illuminants	empty
-----------------------	-------

## EQUIPMENT / ACCESSORIES





– Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

---

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SUBMARINE INTEGRATED SLIM
	Legal information	Legal insert B-not dimmable
	Declarations of conformity	CE Declaration SubMARINE LED Slim Value
	Declarations of conformity UKCA	Fixed LUM

---

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075266414	Folding box 1	42 mm x 58 mm x 1,232 mm	318.00 g	3.00 dm <sup>3</sup>
4058075266421	Shipping box 20	1,280 mm x 249 mm x 225 mm	7203.00 g	71.71 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.